

# HIGH SOLIDS FLOOR FINISH

Sólidos Altos, Alto Rendimiento Final Extendido Del Desgaste

Item #: JSN-120903 | Size: 2.5 Gal

**Vinyl Tile**  
Azulejo del vinilo

**Linoleum**  
Linóleo

**Terrazzo**  
Terrazo

**Concrete**  
Hormigón

**Slate**  
Pizarra

## DESCRIPTION

A high solids floor finish that provides diamond like clarity and brilliant gloss, along with extended wear properties never before available in one product. Will respond beautifully to conventional, high, or ultra-high speed floor equipment after weeks of wear and traffic when used with a spray buff or mop-on restorer. Saves enormous amounts of time and labor by requiring less maintenance.

## FEATURES

- Extended wear
- High Solids
- Low maintenance
- "Wet look" gloss

## BENEFITS

- Longer floor finish life cycle
- Requires less coats
- Saves time and labor
- Floors look great

## AREAS OF USE:

- Classrooms
- Healthcare facilities
- Office buildings
- Hallways
- Entrances
- Hospitals
- Vinyl Tiles
- Linoleum
- Terrazzo
- Slate
- Concrete



FLOOR COATING AND FINISHING  
MATERIAL AS TO SLIP  
RESISTANCE ONLY 17SU

101 Poplar Street • Scranton, PA 18509

 **1-800-834-1019**  **OP1.COM**

JSN-SPEC-03



# HIGH SOLIDS FLOOR FINISH

Sólidos Altos, Alto Rendimiento Final Extendido Del Desgaste

## SPECIFICATIONS:

**Color:**

White

**Odor:**

Fragrance Free

**pH:**

8.0 – 9.0

**Non-Volatile Solids:**

24%

**Coverage:**

1800 – 2200 ft<sup>2</sup> / gal.

**Recommended Coats:**

4

**Dry/Recoat Time:**

30 minutes min.

**Maintenance Schedule:**

Monthly burnish or spray buff

**Slip Resistance:**

0.5 min. by ASTM-D2047

**Storage/Stability:**

1 year

**Weight Per Gallon:**

8.60 lbs./gal.

**Freeze/Thaw Stability:**

3 cycles

## DIRECTIONS:

**PREPARATION:** If stripping is necessary, use a high quality stripper and follow the directions accordingly. Follow with a thorough rinsing and allow floor to dry completely.

If stripping is not necessary; sweep up loose dirt and dust. Clean with a quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow floor to dry completely.

**FINISHING:** Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Four coats is ideal initially, depending on the condition of the floor and desired gloss.

**MAINTENANCE:** The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.

### HAZARD STATEMENTS

This product is not classified as hazardous according to OSHA 29CFR 1910.1200 (HazCom 2012-GHS)

### PRECAUTIONARY STATEMENTS

Do not get in eyes, on skin, or on clothing.

Keep out of reach of children.

Wash thoroughly after handling.

### FIRST AID

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

### STORAGE

Keep container closed to prevent drying out.

Avoid contact with skin and eyes. Wash hands before eating, drinking, smoking or using toilet facilities.

Close container after use.

### SPILL/LEAK

Avoid walking in product. Wipe up or otherwise flush to sanitary sewer.

### DISPOSAL

Dispose of contents/container in accordance with local, state and federal regulations.

### INGREDIENTS

Acrylate Copolymer - (TS), Diethylene Glycol Ethyl Ether - (111-90-0), Tributoxyethyl Phosphate - (78-51-3), Oxidized Polyethylene - (68441-17-8), 2,2,4-trimethyl-1,3-pentanediol disobutyrate, - (6846-50-0), 2,5-furandione, polymer with propene - (25722-45-6), Water - (7732-18-5)

Rev. 1.1.0

101 Poplar Street • Scranton, PA 18509



1-800-834-1019



OP1.COM

JSN-SPEC-03



One  
Point™

CLEAN SOLUTION